

Reports (1)

Inhaltsverzeichnis

- [1 Short description](#)
- [2 Detailed configurationvariables](#)
- [3 Zusätzliche Konfigurationsinstruktionen](#)
- [4 Configurationoverview](#)

Allows to report players. The [reports](#) can be saved (logfile, database) or admins can be notified directly (via E-Mail, [TS3](#)).

1 Short description

Allows to report players. The `[lexicon='reports',"]` can be saved (logfile, database) or admins can be notified directly (via E-Mail, `[lexicon='TS3',"]`).

```
!report NICK MESSAGE
!report Anton He is a cheater
```

== Configurationoverview ==

JavaScript: onfig/plugins/reports.json

```
{
```

```
mailmessage""The player<FROM> just reported <TARGET> with the following message<MESSAGE>" ,
```

```
    "ts3pokemessage": "GSManager: '<FROM>' reported '<TARGET>': <MESSAGE>",
```

```
    "ts3textmessage": "GSManager: '<FROM>' reported '<TARGET>': <MESSAGE>",
```

```
  }
}
```

Alles anzeigen

2 Detailed configurationvariables

<u>Variable</u>	<u>Allowed Values</u>	<u>Description</u>
enabled	truefalse	You can (de)active the plugin with this variable.
database	truefalse	You can save <code>[lexicon='reports',"]</code> to the database by using this variable.
decaytime	Amount	The time in seconds after a player can send another report.
logfile	truefalse	You can save <code>[lexicon='reports',"]</code> to the logfile by using this variable.

mail	truefalse	You can receive E-Mails by using this variable.
mailmessage	String	The message of the E-Mail. Allowed placeholders are <FROM>, <TARGET> and <MESSAGE>.
mailrecipients	String-Array	The receiver of the E-Mail.
mailsubject	String	The subject of the E-Mail.
ts3poke	truefalse	You will be poked in TS by using this variable.
ts3pokemessage	String	The message of the poke. Allowed placeholders are <FROM>, <TARGET> and <MESSAGE>.
ts3pokeuids	String-Array	All UID's of the admins, which should receive the poke.
ts3text	truefalse	You will receive a PM in TS by using this variable.
ts3textmessage	String	The message of the PM. Allowed placeholders are <FROM>, <TARGET> and <MESSAGE>.
ts3textuids	String-Array	All UID's of the admins, which should receive the PM.

3 Zusätzliche Konfigurationsinstruktionen

If you want to use the [lexicon=[TS3](#),'"/>]lexicon] function, you need to create a connection between [lexicon=[TS3](#),'"/>]lexicon]-Server and GSManager. You may visit the [specific documentation](#). You can find the UID's in TS: Settings => Identities. Select the profile on the left side to copy the Unique ID.

4 Configurationoverview

This is an example to see how to add multiple receivers:

JavaScript: config/plugins/reports.json

```
{
  "mailmessage": "The player <FROM> just reported <TARGET> with the following message <MESSAGE> ",
  "ts3pokemessage": "GSManager: ' <FROM>' reported ' <TARGET> ': <MESSAGE> ",
  "ts3textmessage": "GSManager: ' <FROM>' reported ' <TARGET> ': <MESSAGE> ",
}
```

Alles anzeigen