Reports (1)

Inhaltsverzeichnis

- 1 Short description
- 2 Detailed configurationvariables
- 3 Zusätzliche Konfigurationsinstruktionen
- 4 Configurationoverview

Allows to report players. The reports can be saved (logfile, database) or admins can be notified directly (via E-Mail, TS3).

1 Short description

Allows to report players. The [lexicon='reports',''][/lexicon] can be saved (logfile, database) or admins can be notified directly (via E-Mail, [lexicon='TS3',''][/lexicon]).

```
!report NICK MESSAGE
!report Anton He is a cheater
```

== Configurationoverview =

JavaScript: onfig/plugins/reports.json

```
{
```

```
mailmessage": "The player <FROM> just reported <TARGET> with the following message <MESSAGE>",
```

```
            "ts3pokemessage": "GSManager: '<FROM>' reported '<TARGET>': <MESSAGE>",

            "ts3textmessage": "GSManager: '<FROM>' reported '<TARGET>': <MESSAGE>",
    }
}
```

Alles anzeigen

2 Detailed configurationvariables

Variable	Allowed Values	Description
enabled	truefalse	You can (de)active the plugin with this variable.
database	truefalse	You can save [lexicon='reports',''][/lexicon] to the database by using this variable.
decaytime	Amount	The time in seconds after a player can send another report.
logfile	truefalse	You can save [lexicon='reports',''][/lexicon] to the logfile by using this variable.

mail	truefalse	You can receive E-Mails by using this variable.
mailmessage	String	The message of the E-Mail. Allowed placeholders are <FROM>, <TARGET> and <MESSAGE>.
mailrecipients	String-Array	The receiver of the E-Mail.
mailsubject	String	The subject of the E-Mail.
ts3poke	truefalse	You will be poked in TS by using this variable.
ts3pokemessage	String	The message of the poke. Allowed placeholders are <FROM>, <TARGET> and <MESSAGE>.
ts3pokeuids	String-Array	All UID's of the admins, which should receive the poke.
ts3text	truefalse	You will receive a PM in TS by using this variable.
ts3textmessage	String	The message of the PM. Allowed placeholders are <FROM>, <TARGET> and <MESSAGE>.
ts3textuids	String-Array	All UID's of the admins, which should receive the PM.

3 Zusätzliche Konfigurationsinstruktionen

If you want to use the [lexicon='TS3',''][/lexicon] function, you need to create a connection between [lexicon='TS3',''][/lexicon]-Server and GSManager. You may visit the specific documentation.
You can find the UID's in TS: `Settings => Identities`. Select the profile on the left side to copy the `Unique ID`.

4 Configurationoverview

This is an example to see how to add multiple receivers:

JavaScript: config/plugins/reports.json

```
{
```

```
mailmessage": "The player <FROM> just reported <TARGET> with the following message <MESSAGE>",
```

```
            "ts3pokemessage": "GSManager: '<FROM>' reported '<TARGET>': <MESSAGE>",

            "ts3textmessage": "GSManager: '<FROM>' reported '<TARGET>': <MESSAGE>",
    }
}
```

Alles anzeigen